



Battery for GY-HC500 series

BN-VC2128/BN-VC296

Battery Charger for BN-VC2128/BN-VC296

AA-VC2 / AA-VC20



BN-VC2128



BN-VC296



AA-VC2 / AA-VC20

Battery for CONNECTED CAM GY-HC500 series.
2 type battery and battery charger.

GENERAL SPECIFICATIONS

Model	BN-VC2128	BN-VC296
Type	Lithium Ion Battery	Lithium Ion Battery
Description	Battery for GY-HC500 series	Battery for GY-HC500 series
Battery Capacity	12800 mAh, 92 Wh	9600 mAh, 69 Wh
Voltage	7.2 V	7.2 V
Deimensions	42 mm x 72 mm x 93 mm	42 mm x 72 mm x 69 mm
Weight	455g	342 g
Operating temperature	0 °C to 40 °C	0 °C to 40 °C
Storage temperature	-20 °C to 50 °C	-20 °C to 50 °C

GENERAL SPECIFICATIONS

Model	AA-VC2U AA-VC2E AA-VC2EC	AA-VC20U AA-VC20E AA-VC20EC
Description	Battery Charger for BN-VC296G/BN-VC2128	
Input Voltage	AC 100-240V 50/60Hz	
Status	LED charged indicator included	LED charged indicator included
Dimensions	131 mm x 40 mm x 103 mm	131 mm x 40 mm x 103 mm
Weight	Approx. 150 g	
Charging time	BN-VC296G Approx 430 minutes (2ch simultaneous charging) 	BN-VC296G Approx 430 minutes (2ch simultaneous charging) 
		BN-VC296G Approx 300 minutes (single charging) 
Operating temperature	0 °C to 40 °C	0 °C to 40 °C
Storage temperature	-20 °C to 60 °C	-20 °C to 60 °C
Provided accessories	Power code (U model:1, E model:2, EC model:1)	Power code (U model:1, E model:2, EC model:1)

Dimension

