

# DT-X7HUx2

## 7-inch×2 Full HD 4K-HDMI Rack LCD Monitor



- ◆ 7" LCD×2, 1920×1200 resolution, non-glaring
- ◆ Standard 19" 3RU rack install, ±30° rotatable
- ◆ 2K/3G/HD/SD-SDI, HDMI 2.0 (4K60p) monitoring
- ◆ Up to 16-ch embedded audio meters with alert
- ◆ Select any 2 audio channels to output
- ◆ 9 steps quick zoom-in and mapping
- ◆ Peaking focus assist with precision adjustment
- ◆ Build-in multi-camera logs to Rec.709 conversion
- ◆ User 3DLUT cube file import by USB
- ◆ Zebra stripes, False color, R/G/B/Mono
- ◆ H/V delay, AFD, Timecode display
- ◆ Marker 4:3, 13:9, 14:9, 15:9, 1.85:1, 2.35:1
- ◆ Front TALLY light and GPI control
- ◆ USB firmware upgrade

### ■ Specifications:

	Model	DT-X7HUx2
<b>Picture</b>	LCD size	7-inch×2
	Resolution	1920×1200
	Aspect ratio	16:9 / 4:3
	Viewing angle	H/V:160°/160°
	Brightness / Contrast	400cd/m <sup>2</sup> , 1000:1
<b>Input (each LCD)</b>	SDI	2K/3G/HD/SD-SDI ×2
	HDMI	4K60p HDMI 2.0 ×1
	USB (Firmware & LUT)	USB ×1
<b>Output (each LCD)</b>	SDI loop out	2K/3G/HD/SD-SDI ×1
	HDMI loop out	4K60p HDMI 2.0 ×1
	Analog audio	3.5mm socket ×1
<b>General</b>	Power consumption	≤26W (HD); ≤29W (4K)
	Working voltage	DC 6.5-36V
	Working environment	0°- +40°C temperature, 10%-90% humidity
	Dimension	483×132×80mm, 3RU
	Weight (main body)	2.1kg